Pharmacy Connect Refrigerator

with Cloud Connectivity

158L Pharmacy Connect Upright Fridge with Solid Door

| GDMAcode | |
|----------|---|
| SKU code | _ |

PCSR158CT-DWP-UK





Key features

- ✓ Remote temperature recording and adjustment
- \checkmark Power failure alarm with backup battery powered recording
- \checkmark Solid and glass door options

 \checkmark Intelligent fan management system for enhanced performance





Remote temperature monitoring, adjustment, and alarm history via encrypted secure cloud storage over a wireless or Bluetooth connection. Power failure alarm with battery back-up, providing continuous temperature monitoring in the event of a power outage.





Contactless remote monitoring of air and load temperatures via smart phone app or online portal. Schedule automatic temperature reports that can be downloaded directly to your device.



Intelligent Fan Management

Smart fan optimisation aides in temperature stability following door openings, minimising fan activity when door is open to reduce the rate of temperature increase.



Dual Probe Temperature Monitoring

Our dual probe system offers greater temperature accuracy within your appliance, simultaneously measuring both air and product temperatures.



Calibration Certified

All Pharmacy Connect appliances come complete with a calibration certificate, prevalidated using UKAS traceable equipment.



The Experts in Medical Refrigeration

www.lec-medical.co.uk

1of2

Specification: 158L Pharmacy Connect Upright Fridge with Solid Door

| Des Segurity Streng Del. Dels Extensil Volger Imm) Golderm Viel Extensil Volger Imm) Golderm Dels Extensil Volger Imm) Golderm Status It Viel Extensil Volger Imm< | Gross Capacity (litres) | 158L |
|--|--|---|
| Unit Birstant Jogit FromPiperineUnit Birstant Jogit From4400000000000000000000000000000000000 | | |
| Unit Enserrational post from6.000000000000000000000000000000000000 | | |
| Unit ExtensionBitcherminDataset Weigh (mod)3.5.3.4.3.4.3.4.3.4.3.4.3.4.3.4.3.4.3.4. | | |
| Packet With (m)4 5/4/gRedet With (m)6 6/6/m1Redet With (m)6 6/6/m1Redet With (m)10/5/m1Redet With (m)10/5/m1Redet With (m)0.5/m1Scatter of Pain0.5/m1Scatter of P | | |
| Packed Weight mon)6.6.0mmPacked Fight mon)6.9.0mmPacked Fight mon)7.9.0mmPacked Fight mon)7.9.0mmPacked Fight mon)7.9.0mmPacked Packed Pac | | |
| Backs Depin tron)640mmPacks Height Tool000mmPacks Height Tool <th></th> <th></th> | | |
| Backer Weight (mol)J (mm.)Cautory of vigoG.72 Gkg.Cautory of vigoG.72 Gkg.Cautory of vigoG.72 Gkg.ColorM.72 Gkg.ColorM.72 Gkg.ColorM.72 Gkg.ColorP.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color TayS.81 Gkg.Color Gkg.S.81 Gkg.Color Gk | | |
| Packer Workpit bajSTP bitsInternal Dismakois (and) MODH]JUDIN in Keyermin Key | | |
| Control provides(N°Internal Directions (Internal Vestors)(2000)Internal Directions (Internal Vestors)(2000)Colur(200 | | |
| International proof (Notice)Section 1CalourC | | |
| Temperature Bane | | |
| CalourChinal relationWhite/greenEnsume lensingHistons StealInterner Ishih111557Tore of platesSis Sis Oct Histons StealDoor FindsSis Sis Oct Histons StealDoor FindsSis Sis Oct Histons StealDoor FindsHistons StealDoor FindsHistons StealDoor Gran Of TrysName of Door TrysNumber of Door Trys PositionsName of Door TrysDoor Gran Of TrysName of Door TrysNumber of Door StealName of Door TrysOne Or Gran Of StrainYes JackBoor Gran Of StrainYes JackOne Or Gran Of StrainYes JackOne Or Gran Of StrainYes JackDoor Gran | | |
| Examel InlinkParted StellType of plankBH200 (PH2/BH2 mA)Oper TopicStell200 (PH2/BH2 mA)Door TopicStell20 (PH2/BH2 mA)Nomber of Door TopicPh2/BH2 mA)Nomber of Door TopicPh2/BH2 mA)Door Good Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20YesOpen Door Stell20PH2/BH2Open Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Door Stell20Ph2/BH2Open Door Stell20Ph2/BH2Open Door Stell20YesDoor Stel | | |
| internal finithHHP*Doer finithSPLB200 (HES/ABS mig)Doer finithParined Stable/SolidDoer finithSpLB4/ClassDoer finithFilinget ReversiteDoer finithFilinget ReversiteDoer finithRelDoer finithRelSolid / ClassRelNorther of Doer TingeRelSolid StableNoDoer tinerRelSolid StableNoReplement Doer SeelYesDoer StableYesDoer StableYesDoer Seel StableNoReplement Doer SeelYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesDoer StableYesStable AlerneYesTemperature Doer Stable OneYesTemperature Doer Stable OneYesStable AlerneYesStable AlerneYesTemperature Doer Stable OneYesStable AlerneYesStable AlerneYes <t< th=""><th></th><th></th></t<> | | |
| Type of plashieSPL 800 (HP4585 m/m)Door TinksPlanted Steel / SolidDoor TinksSolid / Clisss.Door TaysSolid / Clisss.Door TaysFile (Steel / Solid / Clisss.)Door TaysNumber of Door Tays PacificanNumber of Door TaysNumber of Door Tays PacificanNumber of Door TaysNumber of Door TaysYes 2 MoresPactode LossNeg | | |
| base rinkihPeinred Statie/ SolidBort TypeSolid / ClarksBort SykInged, RunkershikBort SykNumber of Door TragNumber of Door TragNumber of Door TragNumber of Door TragNumber of Door TragBort SykNumber of SykBort SykNumber of SykBort SykNumber of SykBort SykNumber of SykSykNumber of SykSykNumber of SykBort SykNumber of SykSykNumber of Sy | | |
| Deer typeSoled/OpsyDeer typeFigueDeer typeFigueNumber of Door Tryp PatilonsNNumber of Door Tryp PatilonsNBead concerpson Deprint PatheticsNReplacement Door SeelNBead concerpson Deprint PatheticsNReplacement Door SeelNBead concerpson Deprint Door SeelNReplacement Door SeelN <th></th> <th></th> | | |
| Door StyleHinge Hinge HingeNumber of Door TrysNameNumber of Door TrysNameNumber of Door TrysNameNumber of Door TrysNameNumber of Door StylestionsNameDoor Open StylestionsNameDoor StansorNameDoor StansorNameStansorNameStansorNameStansorNameDoor StansorNameDoor StansorName< | | |
| Doer lane"PartNumber of Door Tray PositionsNANumber of Door Tray PositionsNABealescenter Door SealYesDoor Open Door SearYesGene Door SearsYesLockYesAdvalable Feet fummer & positionsYesBerthole SizeYesBerthole SizeYesDrower Size (mol Woch)YesDrower Size (mol Woch)Yes | | |
| Number of Door Tryp N/0 Number of Door Tryp Stabilins N/0 Door Oper Depth (mm) N/0 Door Oper Sensor Ves. Open Door Sensor Ves. Lock Ves. Open Door Sensor Ves. Lock Ves. Adjustable Feet (number & position) 4.Al.Algustable Dorthole Location Reproduct Adjustable Dorthole Location Reproduct Adjustable Temperature Dipply on Panel Ves. Temperature Disply on Panel Ves. Temperature Disply on Panel Ves. Number of Shelf Positions Ves. Shelf Adam Contactis Ves. Number of Shelf Positions Yes. Shelf Adarial Ves. Draver Statin (Wochd) Adjustable Draver Statin (Wochd) Notaction Draver Statin (Wochd) Notaction Draver Statin (Wochd) Notaction Draver Statin (Wochd) Notaction Draver Statin (Notachi) Notaction Draver Statin (Notachi) Notaction< | | |
| Number of box Tray bashionsNyBeplexement Door SealNy6.Beplexement Door SealYes.Box Door Searsont Door SealYes.Gone Door Searsont Door SealYes.Seal Control SealYes.Borthol SizeYes.Borthol SizeBortholBorthol SizeBortholBorthol SizeBortholBorthol SizeYes.Borthol Size <t< th=""><th></th><th></th></t<> | | |
| Door Open Depth (mm)IBDnmReplement Door SalorYesOpen Door SanorYesAdjustable Feet (number & position)4.4.1.4.1.5.1.5.1.5.1.5.1.5.1.5.1.5.1.5. | | |
| Replexement Door Seal Yes Open Door Senor Yes Lack Yes, 2 Keys Adjustable Fer, Gimber & Spotton A All adjustable Rev Porthole Yes Porthole Size Ib mm Porthole Size Yes Remote Alarm Constas Yes Number of Stables/Dravers 4 Number of Stables/Dravers 4 Number of Stables/Dravers 7 Sheff Size (rm) (WxDzH) Ib Methode Draver Statis (rm) (WxDzH) Ib Methode Draver Statis Ib Polythene Coated Wire Draver Statis Ib Methode Draver Statis Ib Polythene Coated Wire Draver S | | |
| Open Door SensorYesLockYes, 2 KeyaAdjustable Fest (number & position)A Al AdjustablePorthole StarIf mmPorthole StarIf mmPorthole StarIf mmPorthole StarIf mmTemperatura Diplay on PanelYesTemperatura Display on FanelYesTemperatura Display on FanelYesTemperatura Display on FanelYesRemeta AdamYesRemeta AdamYesRemeta AdamYesNumber of ShelveSDawers4Number of ShelveSDawers4Number of ShelveSDawers4Number of ShelveSDawers6Shelf Star (mm) (Mobd)Polythene Coated WireDowers Star (mm) (Mobd)NoDowers Star (mm) (Mobd)NoDowers Star (mm) (Mobd)NoDataset Star (mm) (Mobd)No | | |
| LockWys.2 KeysAdutable Fer (Imper & position)4.4 Ind vig/xabbleBorthole Size16 mmBorthole Size19 mmBorthole Size19 mmSize Size Size Size Size Size Size Size | • | |
| Adjustable All adjustable Porthole Ves Porthole Size IS mm Porthole Size Borthole Porthole Size Borthole Temperature Dipoly on Puel Yes Temperature Dipoly on Puel Yes Remote Alum Contacts Yes Remote Alum Contacts Yes Number of Shube/Showers 4 Number of Shube/Showers 5 Sheff Material Polythener Contacts Number of Shube/Showers 4 Number of Shube/Showers 5 Sheff Material Polythener Contact Wire Drawer Material Nomber of Shube/Shom Xfirm Drawer Size (mm) (Wobdh) Polythener Contact Wire Drawer Size (mm) (Wobdh) Yes | • | |
| Decthole Yes Borthole iscation Bern M Borthole iscation Fear Bortom Borthole iscation Yes Temperature Diagno Phanel Yes Temperature Alarm Yes Borthole iscontacts Yes Audibe Alarma Yes Vauia Marria Yes Number of Shelf Positions 4 Shelf Material Posytheme Casted Wire Drawer Size (rmm) (WADAH) Alafferia x 405mm x 6mm Shelf Material Polytheme Casted Wire Drawer Size (rmm) (WADAH) Alafferia Drawer Material Polytheme Casted Wire Drawer Size (rmm) (WADAH) Alarma Drawer Size (rmm) (WADAH) Alarma Drawer Size (rmm) (WADAH) Polytheme Casted Wire Basket Size (rmm) (WADAH) Alarma Drawer Size (rmm) (WADAH) Alarma Drawer Size (rmm) (WADAH) Polytheme Casted Wire Basket Size (rmm) (WADAH) Alarma Drawer Size (rmm) (WADAH) Yes Drawer Size (rmm) (WADAH) Yes Bas | | |
| perthole SizeIs runPerthole LocalitationRear BrattomTemperature Display on PanelYesTemperature Display on PanelYesTemperature Display on PanelYesTemperature Display on PanelYesTemperature Display on PanelYesRende Alarm ContactsYesAudibe AlarmsYesAudibe AlarmsYesNumber of Shelves/Dravers4Number of Shelves/Dravers4Shelf Sice (nm) (WxDxH)AdStrim x 4dStrim x | | |
| PerthelicationRest BatromTemperature Display on PanelYesTemperature Display on PanelYesRemote Alarm ContatsYesAudible AlarmsYesNumber of SheviewSonwers4Number of SheviewSonwers4Number of SheviewSonwers4Number of SheviewSonwers4Shef Meditions5Shef Steirmon (Wabath)496mm x 405mm x 6mmShef Steirmon (Wabath)496mm x 405mm x 6mmShef Meditions10Shef Meditions10Shef Meditions10Shef Meditions10Shef Meditions10Shef Meditions10Drawer Size (mm) (WADath)10Basket Size (mm) (WADath)10Basket Size (mm) (WADath)10Shef Meditions10Drawer Size (mm) (WADath)10Drawer Size (mm) (WADath)10Basket Size (mm) (WADath)10Basket Size (mm) (WADath)10Drawer Size (mm) (WADath)10Shef MeditionsYesSteir Size (Material)10Basket Size (mm) (WADath)10Basket Size (mm) (WADath)10Size (Size Size | | |
| Temperature Display on PanelYesTemperature Display on PanelYesRemote Jarm ContactsYesRemote Jarm ContactsYesVisual AlarmsYesYaual AlarmsYesNumber of Shafe PationsASheft Size (mm) (WACMI)ASheft Size (mm) (WACMI)Polytheme Coated WireDrawer MaterialPolytheme Coated WireDrawer MaterialPolytheme Coated WireDrawer Size (mm) (WACMI)ABasket MaterialPolytheme Coated WireDrawer Size (mm) (WACMI)ANumber of BasketsPolytheme Coated WireBasket Size (mm) (WACMI)AUpin Patheme Coated WirePolytheme Coated WireBasket Size (mm) (WACMI)AUpin TypeDeor Switch / ControllerUpin TypeDeor Switch / ControllerSpark FreeNoDefort settingDeor Switch / ControllerSpark FreeNoDefort settingYesSpark FreeNoSpark Free <th></th> <th></th> | | |
| Temperature NameYesAudible NamesYesAudible NamesYesAudible NamesYesYesYesYesYesNumber of Shelf Nove/Dravers4Number of Shelf Nove/Dravers4Shelf Saterm(VixOxH)YesShelf Saterm(VixOxH)YesDraver Size (rmm) (VixOxH)YesDraver Size (rmm)YesNome of ProbesZProbe TypeAir & Lord (Slicone Oll)Arribut (rmm)YesNome of ProbesYes | | |
| Benete Alarm Contacts Yes Audible Alarms Yes Vaual Alarms Yes Number of Shelf Positions 4 Number of Shelf Positions 5 Shelf Size (rmn) (WxDxH) 496mm x 405mm x 6mm Drawer Size (rmn) (WxDxH) Polythenc Coated Wire Drawer Size (rmn) (WxDxH) N/a Basket Size (rmn) (WxDxH) 485mm x 255mm x 171mm Basket Size (rmn) (WxDxH) 485mm x 255mm x 171mm Interior Light Polythenc Coated Wire Basket Size (rmn) (WxDxH) 485mm x 255mm x 171mm Interior Light Polythenc Coated Wire Basket Size (rmn) (WxDxH) 485mm x 255mm x 171mm Interior Light Polythenc Coated Wire Basket Size (rmn) (WxDxH) 485mm x 255mm x 171mm Interior Light Polythenc Coated Wire Basket Size (rmn) (WxDxH) 485mm x 255mm x 171mm Interior Light Polythen Coated Size Spark Free Door Swrkth, / Controller< | | |
| Audible NammeYesNumber of ShellPostes/Dravers4Number of ShellPostes/Dravers4Number of Shell Postions5Shell MaterialPolythene Coated WireDraver Size (mm) (WxDxH)496mm x 405mm x 6mmShell MaterialPolythene Coated WireDraver Size (mm) (WxDxH)1Basket Size (mm) (WxDxH)1Basket Size (mm) (WxDxH)1Basket Size (mm) (WxDxH)495mm x 255mm x 17mmBasket Size (mm) (WxDxH)495mm x 255mm x 17mmBasket Size (mm) (WxDxH)495mm x 255mm x 17mmInterior LightYesLight ActivationDoor Switch / ControllerFanNesSpark FreeNesDefrost Beskt Size (mm) (WxDxH)0Batter Size (mm) (WxDxH)0Spark FreeNesLight ActivationDoor Switch / ControllerFanYesSpark FreeNesDefrost Beskt Up/HoursNesButtery Besk Up/HoursYesSurd FreeYesNifiYesNifiYesAmberi FreeNesNifiYesAmberi FreeYesNifi FreeYesNifi FreeYesNifi FreeYesNifi FreeYesNifi FreeYesAmonis FreeYesStart MaperialYesStart MaperialYesStart MaperialYesStart Start MaperialYesStart Start MaperialYes </th <th></th> <th></th> | | |
| Visual AmmeYesNumber of Sheef Positions4Number of Sheef Positions5Sheff Size (mm) (VisDxH)496/mm x 40mm x 6mmSheff Size (mm) (VisDxH)Polythene Coated WireDrawer Size (mm) (VisDxH)N/ADrawer Size (mm) (VisDxH)N/ADrawer Size (mm) (VisDxH)N/ASalet Size (mm) (VisDxH)1Basket MaterialPolythene Coated WireBasket Size (mm) (VisDxH)485mm x 25mm x 77mmInstroir LightPolythene Coated WireBasket MaterialPolythene Coated WireBasket Size (mm) (WisDxH)485mm x 25mm x 77mmInstroir LightPolythene Coated WireBasket MaterialPolythene Coated WireSpark FreeDoor Switch / ControllerFanYesSpark FreeDoor Switch / ControllerBuetoshYesWiFiYesNerdYesNerdYesNerdYesNerdYesNumber of PolosYesNumber of PolosYes | | |
| Number of Shelves/Dravers4Number of Shelf Positions5Shelf MaterialPolythene Coated WireDraver Size (mm) (WxDxH)Polythene Coated WireDraver Size (mm) (WxDxH)Polythene Coated WireDraver Size (mm) (WxDxH)N/aDraver Size (mm) (WxDxH)Polythene Coated WireBasket Size (mm) (WxDxH)Polythene Coated WireBasket Size (mm) (WxDxH)Polythene Coated WireBasket Size (mm) (WxDxH)VesBasket Size (mm) (WxDxH)VesSprit FreeNoDefore StettingDotor Switch / ControllerFanVesSprit FreeNoDefore StettingAuto (Off Cycle)Controller TypeDigital WiFL, ExternalBattery Back Up/HoursVesWiFIVesNumber of Polos2Probe TypeAif & Load (Silicone Oil)Arbient Temperature RangeNoVesVesWiff EfferedVesWiff InterpretorNoOther Plug Types AvailableVesUK 3 Pin PlugAlon (Silicone Oil)Arbient Temperature RangeNoOther Plug Types AvailableVesUK 3 Pin PlugAlon (Silicone Oil)Other Plug Typ | | |
| Number of Shelf Positions5Shelf Steir (mm) (WxDxH)496mm x 405mm x 6mmDrawer Steir (mm) (WxDxH)Polythene Coated WireDrawer Steir (mm) (WxDxH)N/aDrawer MaterialN/aNumber of Baskets1Basket State (mm) (WxDxH)485mm x 100mmBasket State (mm) (WxDxH)485mm x 25mm x 10mmBasket State (mm) (WxDxH)485mm x 25mm x 10mmInterior LightEDDLight ActivationYesSpark FreeAuto (Off Cycle)Controller TypeDigital WFL, ExternalBastery Bask Up/HoursYesNPCYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYesNPGYes< | | |
| Shef Ste (mm) (WXDxH)449cmm x 405cmm x 6 mmShef MaterialPolythene Coated WireDrawer Size (mm) (WXDxH)n/aDrawer Size (mm) (WXDxH)n/aDrawer Stex (mm) (WXDxH)n/aBasket Size (mm) (WXDxH)ABset Size (mm) (WXDxH)Basket Size (mm) (WXDxH)ABset Size (mm) (WXDxH)Interior LightYesLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerFanDoor Switch / ControllerFanNoDefors testingALto (Off Cycle)Controller TypeDigital Wire, ExternalBattery Back Up/HoursYes/24hrs TBCBluetoothYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYesWiFiYes <trr>WiFi<th></th><th></th></trr> | | |
| Shef MatrialPolythene Coated WireDrawer Materialn/aNumber of Basketsn/aNumber of Baskets1Basket MaterialPolythene Coated WireBasket MaterialPolythene Coated WireBasket Material485mm x255mm x17mmInterior LightYesLight TypeLEDLight ActwationDoor Switch / ControllerFanDoor Switch / ControllerSpark FreeNoDefrost settingAuto (Cf Cycle)Controller TypeDigital WiFI, ExternalBatter y Back Up/HoursYesButtor De Switch / Controller TypeYesController TypeDigital WiFI, ExternalBattery Back Up/HoursYesButtor TypeYesNine of ProbesYesNine of ProbesYesRefrigerant TypeNoCfC FreeYesHCC FreeYesKCC FreeYesUK3 Fin PlugYesUK3 Fin PlugYesVoltage SupplyYesVoltage SupplyStandKord SuppleYesKord Supple | | |
| Drawer Size (mm) (Wx0xH) n/a Drawer Material n/a Drawer Material n/a Basket Size (mm) (Wx0xH) Polythene Coated Wire Basket Size (mm) (Wx0xH) 485mm x 25mm x 77mm Interior Light Yes Light Type LED Light Activation Door Switch / Controller Fan Yes - Tangential Spark Free No Defords setting Auto (Off Cycle) Controller Type Digital WiFl, External Bletcoth Yes NFC Yes WiFl Yes Number of Probes Yes Ner Yes Number of Probes Ait & Logo ViFlo Ait & Logo Amber Temperature Bange 10°C: to 32°C Refrigerant Type Ait & Logo KG Free Yes MIC Free Yes MC Free Yes MC Free Yes Mark Long Supply Ait & Long Mono Yes | | |
| Drawer Material n/a Number of Baskets 1 Basket Material Polythene Coated Wire Basket Material Polythene Coated Wire Basket Size (mm) (WXXH) (455mm X77mm) Interior Light Ves Light Type (ED) Light Activation Door Switch / Controller Fan Door Switch / Controller Spark Free Mon Defrost setting Auto (Off Cycle) Controller Type Digital Wirle, External Battery Back Up/Hours Yes Battery Back Up/Hours Yes NFC Yes NiFI Yes Number of Probes 2 Probe Type Air& Load (Silicone Oil) Ambient Temperature Range NPC Cot 0.3°C Refrigerant Type Yes Refrigerant Type Yes <tr< th=""><th></th><th></th></tr<> | | |
| Number of Baskets 1 Basket Material Polythene Coated Wire Basket Size (mm) (WxDxH) A85mm x Z55mm x X71mm Interior Light Ves Light Npe Door Switch / Controller Light Activation Door Switch / Controller Ean No Defrost setting Auto (Dif Cycle) Controller Type Digital WIFL; External Battery Back Up/Hours Ves / Tangential Bluetooth Ves NFC Ves WIFI Ves Number of Probes 2 Probe Type Air & Load (Silicone Oil) Ambient Temperature Range No Refrigerant Type PR600a CFC Free Ves MCC Free Ves MCC Free Yes MCG Yes Yes VK3 Pin Plug No Other Plug Types Available Yes VK3 Pin Plug No Other Plug Types Available Yes VK3 Pin Plug Yes VK3 Pin Plug | | |
| Basket Material Polythene Coated Wire Basket Size (mm) (WxDxH) 485mm x 25mm x 171mm Iterior Light Q455mm x 25mm x 171mm Uight Type Light Coated Wire Light Ype Light Coated Wire Light Activation Door Switch / Controller Fan Door Switch / Controller Spark Free No Defroit setting Auto (Off Cycle) Controller Type Digital WiFl, External Battery Back Up/Hours Yees NFC Yees NIFC Yees NIFC Yees WIFI Yees Number of Probes Q Ref Spee Q Vies Q WIFI Conce Yees Number of Probes Q Ref Spee Q Probe Type Air & Load (Silicore Oil) Ambient Temperature Range Yees MCF C Free Yees MCF C Free Yees MCF Plug Yees MCF Plug Types Available Yees </th <th></th> <th>l/d</th> | | l/d |
| Basket Size (mm) (WxDxH)485mm x 255mm x 171mmInterior LightYesLight ActivationLEDLight ActivationDoor Switch / ControllerFanObor Switch / ControllerSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeObjital W/FL ExternalBatery Back Up/HoursYes 2BluetoothYesNrCYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Armis Consolier TypeYesBittery Back Up/HoursYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Armis Consolier TypeYesBittery Back Up/HoursYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Armis Consolier TypeYesBrifgerant TypeYesBrifgerant TypeYesMEC FreeYesArmonia FreeYesVoltag SupplyYesVoltag SupplyYesInsulation TypeHigh Density Polyurethane FoarnBilavian Types AvailableYesVoltag SupplyYesSupplica LockPCSR158W/FI-DUK-UK ((444411326))Optional Draver SystemPCSR158W/FI-DUK-UK ((444411326)) | | Deluthere Cented Wire |
| Interior LightYesLight ActivationLEDLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerFanYes - TangentialSpark FreeNoDefrost settingAkto (Off Cycle)Controller TypeDigital WIFI, ExternalBattery Back Up/HoursYes/24hrs TBCBluetoothYesNincYesWiFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature RangeOiO°C to 32°CRefrigerant TypeYesHCC FreeYesAmoin Temperature RangeYesUS 3 Pi DigNoOther Pilog SupplyYesVoltage Supply220-240VInsulation Tickness (mm)High Density Polywurethane FoamBowing AgentCyclopentaneAnti Microbial HandleYesWall BraketsNoOptional Draver SystemPCSR158WIFI-DLK-UK (444411326)Optional Draver SystemPCSR158WIFI-DLK-UK (444411326) | | |
| Light TypeLEDLight ActivationDoor Switch / ControllerFanDoor Switch / ControllerSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital WIFL, ExternalBattery Back Up/HoursYesBluetoothYesNFCYesWIFIYesProbe TypeAlt & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeYesHFC FreeYesKFCYesWife TreeYesWife TreeYesWife Temperature Range10°C to 32°CRefrigerant TypeYesKFC FreeYesWife TreeYesKFC FreeYesKFC FreeYesVidage SupplyYesWife TreeYesKG Sent Mich Const | | |
| Light Activation Door Switch / Controller Fan No Spark Free No Defrost setting Auto (Off Cycle) Controller Type Digital WiFl, External Battery Back Up/Hours Yes/Zehns TBC Bluetooth Yes NFC Yes WiFl Yes Number of Probes 2 Probe Type Ait's Load (Silicone Oil) Ambient Temperature Range 10°C' to 32°C Refrigerant Type Yes CFC Free Yes MCC Free Yes Mired Yes US 3 Pin Plug Yes Votage Supply 220-240V Insulation Trickness (mm) Yes Insulation Tickness (mm) 45mm Insulation Tickness (mm) Yes Optional Digital Lock PCSRISWIFI-DUK / UK (444411323) Optional Digital Lock PCSRISWIFI-DUK-/UK (444411326) | | |
| PanYes - TangentialSpark FreeNoDefrost settingAuto (Off Cycle)Controller TypeDigital WIFI, ExternalBattery Back Up/HoursYes/Zkhrs TBCBluetoothYesNFCYesNFCYesNumber of Pobes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C'c to 32°CRefrigerant TypeR600aCFC FreeYesUK StoreYesURTS The Silicone Oil Digital WIFI (Science Oil)Ambient Temperature RangeR600aCFC FreeYesUK StoreYesUK StoreYes <th></th> <th></th> | | |
| Spark Free No Defrost setting Auto (Off Cycle) Controller Type Digital WIFI, External Battery Back Up/Hours Yes/24hrs TBC Bluetooth Yes NFC Yes Number of Probes 2 Probe Type Air & Load (Slicone Oll) Ambient Temperature Range 10°C to 32°C Refrigerant Type Refrigerant Type CFC Free Yes HFC Free Yes UK 3 Pin Plug Yes Other Plug Types Available Yes Voltage Supply 220-240V Insulation Thickness (mm) High Density Polyurethane Foam Blowing Agent Cyclopentane Antil Kicrobial Handle Yes Wall Brackets No Optional Digital Lock PCSR158WIFI-DLK-UK (444411323) | | |
| Defrost setting Auto (Off Cycle) Controller Type Digital WIFI, External Battery Back Up/Hours Yes/24/hrs TBC Bluetooth Yes NFC Yes NIFI Yes Number of Probes 2 Probe Type Alir & Load (Silicone Oil) Ambient Temperature Range 10% C to 32% C Refrigerant Type Re6000a CFC Free Yes Ammonia Free Yes UK3 Pin Plug No Other Plug Type Available Yes Voltage Supply 220-240V Insulation Trickness (mm) High Density Polyurethane Foam Blowing Agent Quectonate Anti Rotobial Handle Yes Wall Brackets No Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | | |
| Controller TypeDigital WIFI, ExternalBattery Back Up/HoursDigital WIFI, ExternalBattery Back Up/HoursYesBluetoothYesNFCYesWIFIYesNumber of Probes2Probe TypeAlia E Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeRe600aCFC FreeYesHCF CreeYesHCF CreeYesMomoia FreeYesVoltage SupplyNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAntil Kircobial HandleYesWall BracketsNoOptional Digital LockPCSRT58WIFI-DUK-UK (444411326) | | |
| Battery Back Up/Hours Yes/24hrs TBC Bluetooth Yes NFC Yes NFC Yes Number of Probes Yes Probe Type Air & Load (Silicone Oil) Ambient Temperature Range 10%C to 32%C Refrigerant Type R600a CFC Free Yes HFC Free Yes Momoin Free Yes UK 3 Pin Plug No Ottar Plug Types Available Yes Voltage Supply 220-240V Insulation Tixkness (mm) 45mm Insulation Type High Density Polyurethane Foam Blowing Agent Cyclopentane Anti Kirobial Handle Yes Wall Brackets No Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | | |
| Bluetooth Yes NFC Yes WIFI Yes WiFi Yes Number of Probes 2 Probe Type Air & Load (Silicone Oil) Ambient Temperature Range 10°C to 32°C Refrigerant Type R600a CFC Free Yes HFC Free Yes HFC Free Yes Mamonia Free Yes K3 Din Plug No Other Plug Types Available Yes Voltage Supply 220-240V Insulation Type High Density Polyurethane Foam Blowing Agent Cyclopentane Antiderabilit Type No Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | | |
| NFCYesWIFIYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Din PlugNoOttare Plug Types AvailableYesVoltage Supply220-240VInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| WiFiYesNumber of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesMomoia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DUK-UK (444411326) | | |
| Number of Probes2Probe TypeAir & Load (Silicone Oil)Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aHFC FreeYesHFC FreeYesHCFC FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Probe TypeAir & Load [Silicone Oil]Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aCFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DUK-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Ambient Temperature Range10°C to 32°CRefrigerant TypeR600aCFC FreeR600aHFC FreeYesHFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DUK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Refrigerant TypeR600aCFC FreeYesHFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)High Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326) | | |
| CFC FreeYesHFC FreeYesArmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnt Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| HFC FreeYesHCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| HCFC FreeYesAmmonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Ammonia FreeYesUK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| UK 3 Pin PlugNoOther Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411326)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Other Plug Types AvailableYesVoltage Supply220-240VInsulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Voltage Supply 220-240V Insulation Thickness (mm) 45mm Insulation Type High Density Polyurethane Foam Blowing Agent Cyclopentane Anti Microbial Handle Yes Wall Brackets No Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | | |
| Insulation Thickness (mm)45mmInsulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Insulation TypeHigh Density Polyurethane FoamBlowing AgentCyclopentaneAnti Microbial HandleYesWall BracketsNoOptional Drawer SystemPCSR158WIFI-DWP-UK (444411323)Optional Digital LockPCSR158WIFI-DLK-UK (444411326) | | |
| Blowing Agent Cyclopentane Anti Microbial Handle Yes Wall Brackets No Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | | |
| Anti Microbial Handle Yes Wall Brackets No Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | | Lligh Danaity Daly wrath and Faana |
| Wall Brackets No Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | Insulation Type | |
| Optional Drawer System PCSR158WIFI-DWP-UK (444411323) Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | Insulation Type Blowing Agent | Cyclopentane |
| Optional Digital Lock PCSR158WIFI-DLK-UK (444411326) | Insulation Type Blowing Agent Anti Microbial Handle | Cyclopentane Yes |
| | Insulation Type Blowing Agent Anti Microbial Handle | Cyclopentane Yes No |
| | Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets | Cyclopentane Yes No PCSR158WIFI-DWP-UK (444411323) |
| | Insulation Type Blowing Agent Anti Microbial Handle Wall Brackets Optional Drawer System | Cyclopentane Yes No PCSR158WIFI-DWP-UK (444411323) |



The Experts in Medical Refrigeration

www.lec-medical.co.uk 💊 0344 815 3742