



White Upright Display Chillers

SPG385 / SPD20HG / SPD20SL



1 Year Parts & Labour Warranty



2-3 Working Days Delivery



UK Service Support



Manufactured In Europe



The Sterling Pro Green SPG385 (single door), SPD20HG and SPD20SL (double door) upright chiller range are perfect for displaying chilled drinks and snacks in commercial environments such as cafés, shops, leisure centre's and staff rooms. With a white exterior and interior finish, this range features an environmentally friendly refrigerant, internal LED lighting, black plastic door frames and PVC coated shelving.

Model	Door Type	Can Capacity	Gross & Nett Capacity		Temperature Range	Refrigerant	Dimensions (mm)		
SPG385	Hinged	406 x 330ml	379 ltrs	368 ltrs	+1°C to +10°C	R600a	W595	D605	H1832
SPD20HG	Hinged	1001 x 330ml	832 ltrs	805 ltrs	+1°C to +10°C	R290a	W980	D740	H2145
SPD20SL	Sliding	1001 x 330ml	832 ltrs	805 ltrs	+1°C to +10°C	R290a	W980	D740	H2145





White Upright Display Chillers

SPG385 / SPD20HG / SPD20SL

Range Specifications

	SPG385 Single Door Chiller	SPD20HG Double Door Chiller	SPD20SL Double Door Chiller
GTIN Code	5060750321102	5060750321089	5060750321096
Exterior Dimensions	W595 x D605 x H1832mm	W980 x D740 x H2145mm	W980 x D740 x H2145mm
Packaged Dimensions	W615 x D640 x H1985mm	W1000 x D760 x H2250mm	W1000 x D760 x H2250mm
Number Of Doors	1	2	2
Door Type	Hinged	Hinged	Sliding
Canopy Display	No	Yes	Yes
Glass Type	Double-glazed tempered glass	Double-glazed tempered glass	Double-glazed tempered glass
Can Capacity	406 x 330ml	1001 x 330ml	1001 x 330ml
Gross/Nett Capacity	379/368 Litres	832/805 Litres	832/805 Litres
Shelving Included	x5 PVC coated wire shelves	x4 PVC coated wire shelves	x4 PVC coated wire shelves
Exterior Finish	White with black door frame	White with black door frame	White with black door frame
Interior Finish	White	White metal	White metal
Temperature Range	+1°C to +10°C	+1°C to +10°C	+1°C to +10°C
Max Ambient	+30°C	+30°C	+30°C
Gross Weight	81kg	171kg	171kg
Refrigerant	R600a	R290a	R290a
Climate Class	4	4	4
Energy Consumption	2.7 kWh/24h	5.0 kWh/24h	5.2 kWh/24h
Power Supply	13 amp plug	13 amp plug	13 amp plug
Voltage	220-240/1N 50HZ	220-240/1N 50HZ	220-240/1N 50HZ
Digital Display	No	No	No
Self Closing Doors	No	No	No
Reversible Doors	No	No	No
Lockable	No	No	No
Light Switch	Yes	Yes	Yes
Lighting Type	LED	LED	LED
Castors	No	No	No
Frost Free	No	No	No