



Pre-painted Stainless Steel exterior and interior

AISI-304 Stainless Steel worktop

40mm thick polystyrene insulation

Tempered and hinged frosted glass

Refrigerated understorage with doors (440x270mm)

Electronic temperature control

Automatic defrost and evaporation system

Power supply: 13 amp single phase plug

Model	Glass Style	Deck Area	Storage Doors	Temperature Range	Refrigerant	Dimensions (mm)		
CVED-8-10-C	Curved	0.47m ²	1	-1°C to +5°C	R290a	W1055	D800	H1230
CVED-8-10-R	Flat	0.47m ²	1	-1°C to +5°C	R290a	W1055	D800	H1230
CVED-8-13-C	Curved	0.59m ²	2	-1°C to +5°C	R290a	W1305	D800	H1230
CVED-8-13-R	Flat	0.59m ²	2	-1°C to +5°C	R290a	W1305	D800	H1230
CVED-8-15-C	Curved	0.70m ²	2	-1°C to +5°C	R290a	W1525	D800	H1230
CVED-8-15-R	Flat	0.70m ²	2	-1°C to +5°C	R290a	W1525	D800	H1230
CVED-8-20-C	Curved	0.94m ²	3	-1°C to +5°C	R290a	W2025	D800	H1230
CVED-8-20-R	Flat	0.94m ²	3	-1°C to +5°C	R290a	W2025	D800	H1230
CVED-8-25-C	Curved	1.19m ²	4	-1°C to +5°C	R290a	W2525	D800	H1230
CVED-8-25-R	Flat	1.19m ²	4	-1°C to +5°C	R290a	W2525	D800	H1230
CVED-8-30-C	Curved	1.41m ²	4	-1°C to +5°C	R290a	W2995	D800	H1230
CVED-8-30-R	Flat	1.41m ²	4	-1°C to +5°C	R290a	W2995	D800	H1230