



## Premium Double Door Gastronorm Cabinets

XPI142V / XNI142V / XPI142 / XNI142

**2** Years Parts & Labour Warranty

**2-3** Working Days Delivery

**UK** Service Support

**Manufactured** In Europe



Available with a climate class 5 or 4 rating, the Sterling Pro Vantage premium double door upright cabinet range is perfect for intensive applications in any busy professional kitchen environment. With a robust and heavy-duty Stainless Steel design and finish, this range features an environmentally friendly R290a refrigerant, 80mm thick (CFC-free) polyurethane insulation, extra large touch screen controllers, self closing doors and forced draft evaporators with anti-corrosion covers.

Model	Type	Gross & Nett Capacity		Temperature Range	Energy Consumption	Climate Class	Energy Rating	Dimensions (mm)		
XPI142V	Fridge	1400 ltrs	962 ltrs	-2°C to +8°C	829 kWh/year	5	C	W1358	D875	H2119
XNI142V	Freezer	1400 ltrs	962 ltrs	-18°C to -22°C	4482 kWh/year	5	D	W1358	D875	H2119
XPI142	Fridge	1400 ltrs	962 ltrs	-2°C to +8°C	540 kWh/year	4	A	W1358	D875	H2119
XNI142	Freezer	1400 ltrs	962 ltrs	-18°C to -22°C	4482 kWh/year	4	D	W1358	D875	H2119



# Premium Double Door Gastronorm Cabinets

**XPI142V / XNI142V / XPI142 / XNI142**




Range Specifications				
	XPI142V Fridge	XNI142V Freezer	XPI142 Fridge	XNI142 Freezer
GTIN Code	5060750321416	5060750321386	5060750321409	5060750321379
Dimensions (mm)	W1358 x D875 x H2119	W1358 x D875 x H2119	W1358 x D875 x H2119	W1358 x D875 x H2119
Packed Dimensions	W1430 x D920 x H2200	W1430 x D920 x H2200	W1430 x D920 x H2200	W1430 x D920 x H2200
Hinge Position	N/A	N/A	N/A	N/A
Gross Capacity	1400 Litres	1400 Litres	1400 Litres	1400 Litres
Nett Capacity	962 Litres	962 Litres	962 Litres	962 Litres
Shelves Supplied	6	6	6	6
Grid Level Positions	24	24	24	24
Exterior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Interior Finish	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Temperature Range	-2°C to +8°C	-18°C to -22°C	-2°C to +8°C	-18°C to -22°C
Max Ambient	+40°C	+40°C	+30°C	+30°C
Refrigerant	R290a	R290a	R290a	R290a
Insulation Thickness	80mm	80mm	80mm	80mm
Energy Rating	C	D	A	D
Climate Class	5	5	4	4
Efficiency Index	68.54%	72.14%	24.66%	72.14%
Energy Consumption	829 kWh/year	4482 kWh/year	540 kWh/year	4482 kWh/year
Power Supply	13 amp plug	13 amp plug	13 amp plug	13 amp plug
Voltage	230/1N 50Hz	230/1N 50Hz	230/1N 50Hz	230/1N 50Hz
Wattage	192W	840W	161W	750W
Cooling System	Forced air	Forced air	Forced air	Forced air
Defrost Type	Automatic	Automatic	Automatic	Automatic
Reversible Doors	No	No	No	No
Self Closing Doors	Yes	Yes	Yes	Yes
Lighting	Yes	Yes	Yes	Yes
Lockable	Yes	Yes	Yes	Yes
Castors	Yes	Yes	Yes	Yes





## Premium Double Door Gastronorm Cabinets

### XPI142V / XNI142V



#### High efficiency components

Low energy compressors, large area evaporators and high performing electronic fans that minimize temperature gains, reducing energy consumption.




#### Integrated Stainless Steel handle

Ergonomic, Stainless Steel made, robust, perfectly integrated handle ensures practical opening of the door that avoids dust and dirt collection and is extremely easy to clean.



#### Insulation - 80mm thickness

80mm thickness CFC-free, high-density (40kg/m<sup>3</sup>) polyurethane insulation, guarantees exceptional, long-term insulation and energy savings in all Vantage cabinets.



#### Intelligent air circulation system

Perfect temperature consistency with its innovative airflow design that encircles the food and ensures its proper conservation.



#### Rounded edge interior

Easier cleaning operations to reduce potential dirt traps and optimum hygiene.



#### Removable door gasket


Removable pull-out/push-in magnetic door gasket to keep maximum hygiene and maintain the insulating properties.



#### Maximum energy savings

The XPI142V refrigerator achieves a C Rating under the conditions defined in climate class 5, ensuring the maximum energy savings.

\*The label complies with the delegated regulation (UE) 2015/1094 of the commission of 5th May 2015




#### Compact controller

Extra large, screen touch controller with energy saving strategy and HACCP alarm system, which allows an easy temperature parameter adjustment ensuring the best food preservation. It also offers a Bluetooth data logger as an option.



#### Evaporation of defrost water

Hot gas coming from the compressor is used to automatically evaporate defrost water, instead of by means of heating elements, achieving even less energy consumption.




#### Internal LED lighting

Low energy consumption LED lighting to display the interior, standard in all Vantage upright models.



#### Stamped guides, sturdy wire grids

Stamped guides with rounded edges enable more convenient cleaning operations without any difficulties. Plastic coated wire grids allow storage of different packaging types and have a maximum loading capacity of up to 40kg.



#### Self closing hinged doors

Hinged doors with automatic return for a perfect closing that minimize temperature gain and reduces energy consumption. Doors have a 120° dwell position and closes automatically at less than 90°. Door hinges are also reversible.

