

Product specification



EP1/2M: 280 Ltr Counter Refrigerator

43-110

Two door meat storage counter

Features and benefits

- A reduced footprint the more compact design of G3 counters allow them to fit in the tightest of kitchen spaces without losing capacity
- Taking the travel out of food preparation and customised to your needs, G3 counters offer unrivalled flexibility and quality.
- High performance cyclopentane foam maintains thermal efficiency for longer
- Fully floating lock provides durable security and prevents lock breakage if the key is left in
- New and improved 'Airlines' ventilation system cools the compressor which reduces running time, saving you energy
- With PureControl, the G3's controller display uses pure LEDs, incorporating InGaN technology, which means it achieves higher resolution, lasts longer all while using less power. Through the simple addition of a gateway, you're connectivity-ready
- High quality 304 stainless steel is used as standard on all doors and unit covers for G3 the gold standard in performance stainless steel – meaning the heaviest usage touchpoints on the product are covered
- Operates efficiently in ambient temperatures of up to 43°C

We use cookies to ensure you get the best experience on our website.

More information.

Accept all

Decline all

Technical

Refrigerant R290

Temperature Meat -2/+2°C

Electrical

230/50/1

supply

Fuse rating 10

(A)

80

Current (A) 1.9

Power (W) 440

Refrigerant mass (g)

Thermal heat 410

rejection (kW)

Build

Finish ext/int 304 S/S & Alu

2

Number of sections

Section Left hinge-Right hinge

configuration

System Integral

Worktop features

Standard

Dimensions

Height (mm) 865

Width (mm) 1365

Depth (mm) 700

Gross volume 280

(ltr)

Net volume

(ltr)

172.3

Braked castors

Leg type

GN size

1/1

114

(kg)

Gross weight 128

Net weight

er weight

(kg)

Energy

Climate Class 5

GWP 3

We use cookies to ensure you get the best experience on our website.

More information.

Footnotes

- Castors not available if product supplied less condensing unit
- 100mm leg option: height ranges from 835 to 865mm (replacement for standard castors). 150mm legs: height ranges from 885 to 935mm
- Adequate airflow must be kept around the counter: 150mm
- Depth with door open is 1113mm

Thank you for your interest in this product. We hope you now have everything you need to choose Foster, however if you have any further questions, please do not hesitate to contact us.

Foster Refrigerator, Oldmedow Road, King's Lynn, Norfolk, PE30 4JU +44 (0)1553 691122 | sales@foster-gamko.com | www.fosterrefrigerator.com

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.

We use cookies to ensure you get the best experience on our website.

More information.