

Staff Room Refrigeration


Countertop Staff Room Refrigerator 47L

GDPA code **BRS50W**
SKU code **444443903**




Key features

- ✓ Automatic defrost - the air is continuously circulated around the inside of the fridge preventing any build up of ice inside the fridge compartment, meaning there will never be any need to defrost the product
- ✓ Reversible door - the door can be hinged from either left or right so you can open for your convenience



Removable door seal

Easy removal of your door seal for cleaning or replacing.



A+ energy rating

10% better efficiency than an A rated product for better kWh consumption and therefore cheaper to run.



2 year commercial warranty

All our staff room fridges come with a 2 year commercial warranty for peace of mind.



Energy efficient R600a gas

Using gas that is less damaging to the environment to help reduce our carbon footprint.

Specification: Countertop Staff Room Refrigerator 46L

Gross Capacity (litres)	46
Net Capacity (litres)	30
Unit External Width (mm)	472
Unit External Depth (mm)	450
Unit External Height (mm)	492
Product Weight (kg)	16
Packed Width (mm)	520
Packed Depth (mm)	465
Packed Height (mm)	530
Packed Weight (kg)	19
Country of Origin	UK
Internal Dimensions (mm) (WxDxH)	406 x 358 x 396
Temperature Range	+0°C to +10°C (set point tolerance + or - 2)
Colour	White
External Finish	White Plastic
Internal Finish	HIPS*
Type of plastic	SRL800 (HIPS/ABS mix)
Door Finish	Solid Plastic
Door Type	Solid
Door Style	Hinged, Reversible
Door Liner	Curved
Door Open Depth (mm)	
Replacement Door Seal	No
Open Door Sensor	Yes
Lock	No
Adjustable Feet (number & position)	2
Porthole	No
Porthole Size	N/A
Porthole Location	N/A
Temperature Display on Panel	No
Temperature Alarm	No
Remote Alarm Contacts	No
Audible Alarms	No
Visual Alarms	No
Number of Shelves	1
Number of Shelf Positions	1
Shelf Size (mm) (WxDxH)	
Shelf Material	Wire
Number of Baskets	0
Basket Material	N/A
Basket Size (mm) (WxDxH)	
Interior Light	No
Light Type	N/A
Light Activation	N/A
Fan	Yes
Spark Free	No
Defrost setting	Auto (Off Cycle)
Controller Type	Manual, Internal
Number of Probes	0
Probe Type	N/A
Ambient Temperature Range	10 to 32
Refrigerant Type	R600a
CFC Free	Yes
HFC Free	Yes
HCFC Free	Yes
Ammonia Free	Yes
UK 3 Pin Plug	Yes
Other Plug Types Available	No
Voltage Supply	220-240
Insulation Thickness (mm)	32
Insulation Type	High Density Polyurethane Foam
Blowing Agent	Cyclopentane
Anti Microbial Handle	No
Wall Brackets	No
Optional Drawer System	No
Optional Digital Lock	No
Other Door Option	No